

Our new terracotta collection,

TUSCANY COTTO

has arrived. Available in two beautiful terracotta colours... a modern twist on a traditional look.



PRODUCT TYPE: Terracotta

COLOURS: Sand and Natural

SIZES: 150x150mm, 60x240mm and 300x300mm

Non-Rectified Edges

FINISHES/USAGE:

AESTHETIC QUALITIES:

TECHNICAL DATA:

Matt/Wall and Floor

Natural Terracotta colours

P4 Pendulum Slip Rating

- Sealing is recommended prior and post grouting for the **60x240mm only.**
- Dark grout colours are not recommended.
- Minimum 5mm grout joints are recommended.

More Technical data is located on the last page.

VARIATION:



V1



PRODUCT INFORMATION




Tuscany Cotto Sand

Matt 300x300mm



Tuscany Cotto Sand

Matt 60x240mm



Tuscany Cotto Natural

Matt 150x150mm | 300x300mm



Tuscany Cotto Natural

Matt 60x240mm



LIFESTYLE IMAGES





TECHNICAL DATA - BRICKS

	technical characteristics	test method	result
۵ ۵ ۵ ۵ ۵	water absorption	ISO 10545-3	5,75%
5	modulus of rupture	ISO 10545-4	27,78 MPa
*	impact resistance	ISO 10545-5	0,80
5	coefficient of thermal expansion	ISO 10545-8	6,4
£07	deep abrasion resistance	ISO 10545-6	275 mm³
	moisture expansion	ISO 10545-10	0,22 mm/m
	resistance to frost	ISO 10545-12	> 100
£03	surface scratch hardness	-	6 Mohs



TECHNICAL DATA - TILES

	technical characteristics	test method	result
۵ ۵ ۵ ۵ ۵	water absorption	ISO 10545-3	7,09%
5	modulus of rupture	ISO 10545-4	20,7 MPa
\Rightarrow	impact resistance	ISO 10545-5	0,80
5	coefficient of thermal expansion	ISO 10545-8	7,4
	deep abrasion resistance	ISO 10545-6	215 mm³
	moisture expansion	ISO 10545-10	0,228 mm/m
	resistance to frost	ISO 10545-12	> 100
	coefficient of friction	-	0,67 dry 0,58 wet